



Wohnraum-Luftentfeuchter

Technische Daten

	Airsec 7 mobil	Airsec 3 mobil	CDF 10 stationär
Artikelnummer	308.01 weiss, 308.03 anthrazit	348.01	333.07
Wasserentzug 10°C / 60% r.F.	4,8 l/24 h	3,3 l/24 h	–
Wasserentzug 15°C / 60% r.F.	6,2 l/24 h	4,2 l/24 h	–
Wasserentzug 20°C / 60% r.F.	9,9 l/24 h	7,8 l/24 h	4,8 l/24 h
Einsatzbereich	750 m ³	700 m ³	80 m ³
Luftdurchsatz	250 m ³ /h	200 m ³ /h	220 m ³ /h
Umgebungstemperatur	5–32 °C	5–32 °C	10–30 °C
Schalldruckpegel 1 m	50 dB (A)	48 dB (A)	46 dB (A)
Kältemittel	R290	R290	R134a
Kältemittelgewicht	95 g	65 g	–
Eimerinhalt	4,5 l	6,5 l	optional: 5,5 l
Spannung	230 VAC	230 VAC	230 VAC
Frequenz	50 Hz	50 Hz	50 Hz
Stromaufnahme	1,15 A	1,89 A	2,1 A
Schutzart	IP 20	IP X0	IP X2
Leistungsaufnahme	210 W	330 W	390 W
Absicherung	10 A/T	10 A/T	10 A/T
Breite	340 mm	340 mm	535 mm
Höhe	501 mm	580 mm	600 mm
Tiefe	320 mm	240 mm	240 mm
Gewicht	16 kg	14,5 kg	28 kg

Airsec 7

308.01 308.03

