



Stationäre Luftentfeuchter für Wandmontage

Technische Daten

	KRK 10	KRK 25	KRK 40
Artikelnummer	312.01	312.03	312.05
Wasserentzug 10 °C / 60 % r. F.	4.8l / 24h	9.6l / 24h	18l / 24h
Wasserentzug 15 °C / 60 % r. F.	7.8l / 24h	17.4l / 24h	33.9l / 24h
Wasserentzug 20 °C / 60 % r. F.	9.9l / 24h	22.2l / 24h	41.4l / 24h
Einsatzbereich	300 m ³	850 m ³	1 200 m ³
Luftdurchsatz	250 m ³ / h	600 m ³ / h	900 m ³ / h
Umgebungstemperatur	2–32 °C	2–32 °C	2–32 °C
Relative Luftfeuchtigkeit Betrieb	40–90 %	40–90 %	40–90 %
Schalldruckpegel 2 m	54 dB(A)	56 dB(A)	55 dB(A)
Kältemittel	R290	R32	R32
Spannung	230 VAC	230 VAC	230 VAC
Frequenz	50 Hz	50 Hz	50 Hz
Stromaufnahme	1.52 A	3.7 A	5.45 A
Schutzart	IP 20	IP 20	IP 20
Leistungsaufnahme	340 W	815 W	1 230 W
Absicherung	10 A/T	10 A/T	10 A/T
Breite	560 mm	560 mm	560 mm
Höhe	323 mm	400 mm	504 mm
Tiefe	416 mm	416 mm	518 mm
Gewicht	22 kg	33 kg	45 kg

