

Aussengeräte Multi



Multi-Split

			RAS-2M18G3AVG-E	RAS-3M18G3AVG-E	RAS-3M26G3AVG-E	RAS-4M27G3AVG-E	RAS-5M34G3AVG-E
Kühlleistung	kW		5.20	5.20	7.00	8.00	10.00
Leistungsaufnahme	kW	❄️	1.6 - 6.5	2.0 - 7.5	2.0 - 9.0	2.0 - 10.0	2.5 - 11.5
Schalldruckpegel (h)	dB (A)	❄️	48	48	49	50	52
Schallleistungspegel	dB (A)	❄️	61	61	62	63	65
SILENT MODE			58	56	56	57	58
Heizleistung	kW	☀️	5.60	6.80	8.70	9.00	12.00
Leistungsaufnahme (min./max.)	kW	☀️	1.3 - 8.2	1.9 - 8.3	2.0 - 11.5	2.0 - 12.0	2.2 - 14.2
Schalldruckpegel (h)	dB(A)	☀️	50	52	53	54	56
Schallleistungspegel	dB(A)	☀️	63	65	66	67	69
SILENT MODE			57	59	58	58	60
Rohrverbindungen (gas - flüssig)	"		2 × 1/4	2 × 1/4, 1 × 1/2	1 × 3/8 + 2 × 1/2	2 × 3/8 + 2 × 1/2	3 × 3/8 + 2 × 1/2
max. Rohrlänge (per Einheit/Total)	m		20/30	25/50	25/70	25/70	25/80
max. Höhenunterschied	m		10	10	15	15	15
Menge Kältemittel vorgefüllt	kg		1.2	1.25	1.90	2.05	2.39
Energieeffizienzklasse		❄️/☀️	A+++ / A++	A+++ / A++	A+++ / A++	A++ / A+	A++ / A+
Abmessungen (H × B × T)	mm		630 × 800 × 300	630 × 800 × 300	890 × 900 × 320	890 × 900 × 320	890 × 900 × 320
Gewicht	kg		43	44	67	68	78

